

PRESENTACIÓN EV CHARGER

Energy solutions



SISTEMAS DE ALIMENTACIÓN DE LITIO



info@bateriasmadrid.com
www.bateriasmadrid.com

Product Introduction



Product parameters:

Single module power: 3.84KWh LifePO4
 Total power: 11.52KWh
 Charging current: 10A/20A
 Output current: 0~50A.
 Output voltage range: DC200V-530V
 Charging gun:GBT(CCS1/CCS2/ChadeMO)
 Gun line length: 5m
 Operation mode: Single-Alone
 System recharge: AC220V/7kw
 LED display: 4.3 inches.
 Control module size: 550*370*171mm
 Battery module size: 550*370*160mm
 Control module weight: 30kg
 Battery module weight: 38kg
 Working temperature: -10°C~ 60°C
 Protection grade: IP54

**Stacked lithium
 battery EV
 charging pile
 11.52KWh/20KW**

Application  Mobile rescue charging



Product Introduction



Product parameters:

Energy storage capacity: 11.5kwh LifePO4
 Output power: 20kw constant power
 Output voltage: DC150V~750V
 Output current: 0 ~ 50 A.
 Man-machine interface:7-inch touch screen
 Charging gun:GBT(CCS1/CCS2/ChadeMO)
 Gun line length: 5m
 Operation mode: Single-Alone
 System recharge: AC220V/AC charging gun
 Product size: 740*465*890mm
 Weight: <160KG
 Working temperature: -10°C~ 60°C
 Protection grade: IP54

**Mobile energy
 storage charging
 pile
 11.5KWH/20KW**

Application  Mobile rescue charging



Product Introduction

Product parameters:



Energy storage capacity: 65kwh LifePO4
 Output power: 60kw
 Output voltage: DC200V~750V
 Output current: 0 ~ 150 A.
 Man-machine interface:7-inch touch screen
 Charging gun:GBT (CCS1/CCS2/ChadeMO)
 Gun line length: 5m
 Operation mode: Single-Alone/OCPP1.6J
 System recharge: AC380V-20kw/DC charging gun fast charge.
 Product size: 1480*900*1400mm
 Weight: <1000KG
 Working temperature: -10°C~ 60°C
 Protection grade: IP54
 Driving mode: Remote control driving
 (Automatic driving module can be upgraded)

**Mobile energy storage
 charging robot
 65KWH/ 60KW**

Application  Mobile charging 



Product Introduction

Product parameters:



Energy storage capacity: 65kwh LifePO4
 Output power: 60kw
 Output voltage: DC200V~750V
 Output current: 0 ~ 150 A.
 Man-machine interface:7-inch touch screen
 Charging gun:GBT(CCS1/CCS2/ChadeMO)
 Gun line length: 7m.
 Operation mode: Single-Alone/OCPP1.6J
 System recharge:DC charge gun fast charge
 Product size: 1250*925*1050mm
 Weight: 766KG.
 Working temperature: -10°C~ 60°C
 Protection grade: IP54

**Mobile energy
 storage charging pile
 65KWH/ 60KW**

Application  Mobile rescue charging 



Product Introduction

Product parameters:



Energy storage capacity: 141kwh LifePO4
 Output power: 120kw constant power
 Output voltage: DC200V~750V
 Output current: 0 ~ 250A
 Man-machine interface:7-inch touch screen
 Charging gun:GBT(CCS1/CCS2/ChadeMO)
 Gun line length: 7m.
 Operation mode: Single-Alone/OCPP1.6J
 System recharge:DC charge gun fast charge
 Product size: 2353*900*840mm
 Weight: 1390KG
 Working temperature: -10°C~ 60°C
 Protection grade: IP54

**Mobile energy storage
 charging pile
 141KWH/120KW**

Application // Mobile rescue charging



Product Introduction

Product parameters:



Energy storage capacity: 161kwh LifePO4
 Output power: 120kw constant power
 Output voltage: DC200V~750V
 Output current: 0 ~ 250A.
 Man-machine interface:7-inch touch screen
 Charging gun:GBT(CCS1/CCS2/ChadeMO)
 Gun line length: 7m.
 Operation mode: Single-Alone/OCPP1.6J
 System recharge:DC charge gun fast charge
 Product size: 2050*1230*1087mm
 Weight: 1500KG
 Working temperature: -10°C~ 60°C
 Protection grade: IP54

**Mobile energy storage
 charging pile
 161KWH/120KW**

Application // Mobile rescue charging



Product Introduction

Product parameters:



Input voltage: AC260V-530V
 Rated power: 20KW
 Output voltage: DC200V-750V
 Output current: 0-50A
 Charging gun line: 5M (customizable)
 LCD: 4.3-inch touch screen
 Charging mode: Touch startup (password)
 DC Charging gun: :GBT (CCS1/CCS2/ChadeMO)
 Size :540*210*520mm
 Weight: 35KG
 Working temperature: -10°C~ 60°C
 Protection grade: IP54

Portable EV charger G2V/20KW

Application // Portable fast charging



Product Introduction

Product parameters:



Inverter: 4000W 220V/110V(continuous 4000W)
 power frequency pure sine wave inverter.
 Battery specification: LifePO4 (3840Wh)
 24V PV IN:support 280w(max.) solar panel
 charging
 DC 12V OUT:Cigarette lighter
 DC 24V IN-OUT:support 50A charger for fast
 charging
 AC output:220V/110V 16A universal socket*2
 5V output: Type-C,USB 3.0 supports wireless
 charging of mobile phones.
 Display screen:Chinese and English interfaces
 are adjustable.
 Product size: 509 * 306 * 459 mm
 Product weight: 42 kg

Multifunctional outdoor high-power portable AC/DC power supply 3840kw/4000W

Application // Emergency rescue, outdoor power supply

